



Mobile Field Shower System

Set up within minutes, Reeves' 4- and 6-Stall Mobile Field Shower Systems make it possible to establish shower facilities anywhere, any time. Created by combining DRASH shelter technology with a state-of-the-art water supply system, this unique, independently operational design includes private shower stalls and a common wash area with wash basins and benches. All Reeves Field Shower Systems are available in blue, green and tan.

READY FOR ANYTHING

800.328.5563
info@ReevesEMS.com
www.ReevesEMS.com

DHS SYSTEMS LLC
A DHS TECHNOLOGIES COMPANY

Mobile Field Shower System

FEATURES:

Shelter System:

- Various shower and sink configurations available to meet users' needs.
- Includes a durable, fire retardant, mold and mildew resistant, water-proof cover.
- Frame is manufactured from Titanite™, an aerospace composite material with superior structural properties.
- Shelter sets up in minutes without the use of special tools.
- Plumbing lines are integrated into the interior shelter frame, allowing for an easier and more rapid set up. The lines are supplied by 35-foot, heavy-duty, abrasion-resistant hoses that connect them to the water heater via cam lock fittings.
- Wash basins and six-foot long benches form the common wash area.
- Individual shower stalls include 2.5 gpm showerheads with quick-connect fittings and built-in shut offs.
- A rigid-wall containment berm features 8" high side walls and raised floors for optimum water runoff conditions.
- "Intellipump" automatically turns on with the presence of water and turns off when level is below ¼ inch.
- Shelter includes five-year warranty for materials and workmanship.

G2 Water Heating System:

- 425,000 BTU, self-heating water system.
- Multi-Fuel (diesel, kerosene, home heating oil, and JP4).
- Flow rate of up to 28 gallons per minute.
- 10-gallon on-board fuel tank with drain plug.
- 110V outlet onboard for convenience.
- Instructional panel for ease of operation.
- Built-in anti-scald protection device factory pre-set at 110°F.
- Thermostatically-controlled.
- Operator's panel with color-coded temperature and pressure gauges.
- Heater ignited by solid state electrical system (NO FLAME) that ignites upon water flow.
- Burner motor is a 1/4 hp, 120 V, 60hz, 1 ph and runs at 3450 rpm.
- Inline GFCI protection.
- Fuel filter with water separator.
- Modular design -- ruggedized for field use.
- Man portable and easy to maneuver.
- Mounted on four (4) hardened tires with hand brake for safety.
- 1 ½" Female NST inlet with swivel and teathered compressed air adapter for winterization purposes.
- Unit will safely accept incoming water pressure of up to 125 psi.
- System can be adapted for use with multiple water sources that provide adequate water pressure and flow (adapters not included).
- Four (4) discharge outlets with male cam lock fittings and tethered caps.
- Includes two (2) 35-foot, ½" supply hoses with cam lock fittings that provide heated water and solution to Reeves shower plumbing.
- Discharge outlets and supply hoses can be factory modified in order to supply heated water to non-Reeves shower systems.

